



564 SS GS2 - Cheat Sheet

The 564 SS GS2 has several new features and characteristics that require special attention during installation and set-up. This unit uses the new GreenSmart 2 system. Refer to the owner's manual for full details.

GreenSmart™ 2

This heater has been updated with the 2013 version of GreenSmart™ 2 components from SIT. These components function in a near identical fashion to the previous 2012 components. The primary differences are:

- The integrated fireplace controller (IFC) now has a built in transformer (120v connected to the IFC).
- When ordering a GreenSmart remote, make sure to order the GreenSmart 2 version:
NG 99300693
LP 99300692
- Fuses are built into the fireplace to protect components (see manual for details).

Refer to the owner's manual for installation details.

Installation Warnings

- **Install Insulation when Converting to Rear Vent Configuration** The insulation is only used for rear vent configurations. Failure to install the insulation will create a safety hazard.
- **FPX Arched Upgrade Kit (98500683) Required When Using Arched Faces** The upgrade kit includes the mounting brackets and tiling guide. It must be installed prior to installing tile or other facing.
- **4" Clearance Above Vent when Rear Vented** See manual for details.
- **Top Vent vs. Rear Vent** Depending upon top or rear vent configuration, maximum vent configuration may change. See installation manual for details.
- **May Use 6-5/8" Vent in Top Vent Configuration** See manual for details.